

Physical Science International Journal 4(8): 1100-1109, 2014

SCIENCEDOMAIN *international www.sciencedomain.org*

Preparation, Microstructural and Optical Characterization of NiO Nanoparticles

M. A. Kaid1*

¹Physics Department, Faculty of Science, El-Minia University, El-Minia, Egypt.

Author's contributions

This work was carried out in collaboration between all authors. All authors read and approved the final manuscript.

Original Research Article

Received 25th April 2014 Accepted 7 th June 2014 Published 21st June 2014

ABSTRACT

A fine NiO powders were prepared by a homogeneous precipitation method with an aqueous solution of nickel nitrate hexahydrate and citric acid. The microstructure, surface morphology of NiO were characterized by thermo gravimetric (TGA) analysis and differential scanning calorimeter (DSC), X-ray diffraction (XRD), scanning electron microscope (SEM) , infrared (IR) spectroscopy. The experiment results show that the NiO nanoparticles are cubic structure with spherical shape and well dispersed, the particle size distribution ranging from 7 to 28nm with the average particle size is about 15.5nm. The infrared absorption band of NiO nanoparticles shows blue shifts compared with that of bulk NiO. The optical band gap energy value 3.81eV has been determined from absorbance spectra in strong absorption region.

Keywords: Nanoparticle NiO; XRD; SEM; crystallite size; energy gap.

1. INTRODUCTION

In recent years, nanomaterials have received growing interests as a result of their peculiar and fascinating properties and applications superior to their bulk counterparts. Nanomaterials have been widely used in various fields, such as photoelectric, recording materials, catalysts, sensors, ceramic materials, etc., due to their special structures and properties [1,2]. A fine nickel oxides are very promising functional materials [3]. They have

^{}Corresponding author: Email: mgalal09@yahoo.com;*

been widely used in the product ion of battery electrodes, catalysts, semiconductor materials (such as piezoresistors, thermistors), the gas sensor materials [4], nickel zinc ferrite [5], stain glass, ceramic additives [6].

Nanostructures nickel and its oxides are of special interest because of their electronic and magnetic properties and their surface chemistry [7,8]. NiO is a stable wide direct band-gap material (3.56eV) and exhibits p-type semiconducting behavior [9]. Nanosized NiO can be superparamagnetic and superanti-ferromagnetic [10]. Such nanostructures have potential applications in catalysis, rechargeable batteries, and fuel cells [11]. Thus the ability to generate such minuscule structures is essential to much of modern science and technology [12-16]. Techniques for the nano-scale particle preparation have been developed in the last years and can be divided into three major classes: chemical, mechano-chemical and thermophysical methods [17,18]. In the present work, NiO phase was prepared using $Ni(NO₃)₂·6H₂O$ and citric acid as the reduction agent by the sol-gel self propagating, low temperature combustion process. The morphology of the NiO was measured using a scan electron microscope (SEM) and X-ray diffractogram. The optical properties of NiO have been determined via absorbance spectrum and the optical band gap has been determined.

2. EXPERIMENTAL

Certain amount of $Ni(NO₃)₂·6H₂O$ was dissolved in distilled water, then 2 mol of citric acid was added for each mol of metal ion and the mixture was heated at 90ºC for 2h. Then the solution was moved to cold water, quenched for 20min and filtrated, washed with deionized water and alcohol three times respectively and dried at 110°C for 2 h to obtain the precursor. The precursor was calcinated at 300~450ºC (according to TGA/DSC curve that mentioned below) for 4h to get superfine NiO powders. The thermal behavior of the precursor was analyzed by thermogravimetric analysis (TGA) and differential scanning calorimetry (DSC) (Shimadzu 50 with an accuracy of ± 0.1 K). The value of the glass transition, T_g , the crystallization extrapolated onset, T_{in} and the crystallization peak, T_p , temperature were determined with accuracy \pm 1K by using the microprocessor of the thermal analyzer. The structure and phases of the powder sample was identified by means of X-ray powder diffraction (XRD) Shimadzu Diffractometer XRD 6000, Japan, with Cu-K α 1 radiation $(\lambda = 1.54056 \text{ Å})$. The data was collected by step-scan modes in a θ -2 θ range between 4° and 80º with step-size of 0.02º and step time of 0.6 seconds. Pure Silicon~Si 99.9999% was used as an internal standard. The surface morphology of nanoparticles was observed by means of a scanning electron microscope SEM (JOEL XL) operating at an accelerating voltage of 30kV. The relative error of determining the indicated elements does not exceed 2%. The IR absorption spectra of the glasses in the wave number range of $400-2000 \text{cm}^{-1}$ with a resolution of 4cm^{-1} were recorded at room temperature by an IR spectrophotometer type JASCO, FT/IR-430 (Japan), using the KBr pellet technique. Optical characterization of the powder sample on transparent plaster has been preformed from spectral absorbance, which was obtained through JASCO V-670 double beam spectrophotometer. The measurements have been performed in the wavelength range from 200 to 2500 nm. The optical properties of NiO have been determined via absorbance spectrum and the optical band gap was determined.

3. RESULTS AND DISCUSSION

Fig. 1 shows thermal curves of the precursor. From the TG curve, it can be seen that except for the weight loss before 200ºC, which is due to loss of physical absorbed water on the surface of the precursor. Most of the weight loss of the precursor takes place between 300ºC and 360ºC, which is caused by the thermal decomposition of the precursor above 400ºC, there is no weight loss at T_G curve, indicating that the decomposition is complete. Accordingly, a strong exothermic peak on DSC curve appears between 335ºC and 365ºC.

Fig. 1a shows the DSC traces for of the precursor at heating rate 10 K/min, this figure displays a crystallization peak, which consists of two overlapped crystallized peaks. Fig. 2 shows the separation of two overlapped crystallized peaks. The indices 1 and 2 in T_{p1} and T_{p2} denote to the first peak and the second peak, respectively. The presence of two peaks means that there are two phases appear during the crystallization process. The phases at which the alloy crystallizes after the thermal process have been identified by X-ray diffraction.

Fig. 1. TGA and DSC curves of the precursor

To identify the possible phases that crystallizes during the thermal treatment applied to the samples, the X-ray diffraction patterns of the precursor annealed at 200, 335, 350 and 365ºC, each one for 2h. Fig. 3a shows the most relevant portions of the diffractgram for the precursor at 200ºC, which show characteristics of the amorphous phase of the precursor at diffraction angles (2θ) between 4 and 70º. To identify the possible phases that crystallizes according to TGA and DSC curves shown in Fig. 1. The X-ray diffraction patterns of the precursor annealed at the first peak of crystallization temperature (T=335ºC) with a heating rate of 10ºC/min for 2h. Fig 3b represents the diffractogram of the transformed material after the crystallization process suggests the presence of nanocrystallites of two phases, the first is Ni according to JCPDS 1-1258, which crystallizes in the cubic structure at 20=44.241° and 51.602º corresponding to C(111) and C(200) orientations with lattice parameters a=b=c= 0.354nm and the second is NiO according to JCPDS 2-1216, which crystallites in the cubic structure at 2θ=37.009º, 43.165º and 62.672º corresponding to C(111), C(200) and C(220) orientations with lattice parameters a=b=c=0.417nm. Fig. 3c shows the X-ray diffraction patterns of the precursor annealed at 350ºC with heating rate of 10ºC/min for 2h. The crystallization process in Fig. 3c suggests the presence of a major of nanocrystallites of NiO phase and small traces of Ni phase. When the annealing temperature increase to second peak of crystallization temperature (T=365ºC that appear in Fig. 2) with a heating rate of 10ºC/min for 2h, only NiO phase appear as shown in Fig. 3d according to the mentioned above JCPDS card.

Fig. 2. DSC traces for Ni/NiO and NiO overlapped phases at heating rate 10^ºK/min

The XRD pattern shows a significant amount of line broadening which is a characteristic of nanoparticles. The crystal size for both Ni and NiO peaks at different temperature of annealing can be calculated according to Debye-Scherrer formula [19].

$$
D = \frac{k\lambda}{\beta\cos\theta} \tag{1}
$$

Where k=0.9, λ is the wavelength of the Cu-Kα radiations, β is the full width at half maximum and θ is the angle obtained from 2θ values corresponding to maximum intensity peak in XRD pattern. The calculated crystallite size value of each peaks are listed in Table 1. It is observed that the crystallite size decreases with increasing the annealing temperature. The decrease in crystallite size may attribute to the increase in the FWHM at each reflection with increasing the annealing temperature [20]. Such an increase in FWHM may be owing to the decreasing in lattice defects among the grain boundary. Bragg's law was used to calculate inter planar space [21].

		$T = 335$ °C		
Pos. $[2\theta^o]$	d-spacing [Å]	FWHM	Crystallite Size (nm)	Related peak
37.009	2.4291	0.4133	21.162	NiO
43.165	2.0959	0.3822	23.337	NiO
44.241	2.0474	0.4133	21.663	ΝI
51.602	1.7713	0.4326	21.296	Ni
62.672	1.4824	0.4810	20.188	NIO
		$T = 350^{\circ}C$		
Pos. [2 θ ^o]	d-spacing [Å]	FWHM	Crystallite Size (nm)	Related peak
37.009	2.4022	0.4452	19.671	NiO
43.165	2.1034	0.4372	20.390	NiO
44.241	2.0486	0.4991	17.937	NI
62.672	1.4826	0.5122	18.952	NIO
		$T = 365$ °C		
Pos. $[2\theta^o]$	d-spacing [Å]	FWHM	Crystallite Size (nm)	Related peak
37.176	2.4186	0.5904	14.822	NiO
43.244	2.0922	0.5532	16.128	NiO
43.244	1.4859	0.7200	13.471	NIO
		$n\lambda = 2d \sin(\theta)$		(2)

Table 1. Full width at half maximum and crystallize size of Ni/NiO and NiO nanoparticle phases with different annealing temperature

Fig. 4 shows the SEM image of NiO nanoparticles at annealing temperature 365ºC with magnification of 70000 X. From the data obtained by SEM micrographs, the particle size histograms can be drawn and the mean size of the particles can be determined using SEM with developed software (Image Processing and Analysis in Java) [22]. Fig. 5 shows the particle size distribution of NiO nanoparticles. It can be seen that the particle sizes possess a small and narrow size distribution in a range from 7 to 28nm, and the mean diameter (taken as average particle diameter) is about 15.5nm. The mean particle size determined by SEM is in good agreement with the average crystallite size calculated by the Scherer formula from the XRD patterns [23]. However, at this magnification, it is clear to see that many nanoparticles are absorbed on the surface of large particles to form aggregates. This is because those small particles have big surface area, high surface free energy, and unstable structure, and can gather easily to form big aggregates in order to reduce their surface energy.

Fig. 3. X-ray diffraction spectra of precursor at different annealing temperatures at different

Fig. 4. SEM image of NiO nanoparticles

Fig. 5. Particle size distribution of NiO nanoparticles

Fig. 6 shows the IR spectra of NiO nanoparticles, which showed several significant absorption peaks. The broad absorption band in the region of 600–700cm⁻¹ is assigned to Ni–O stretching vibration mode; the broadness of the absorption band indicates that the NiO powders are nanocrystals. The size of samples used in this study was much less than the bulks form NiO, so that NiO nanoparticles had its IR peak of Ni–O stretching vibration and shifted to blue spectrum. Due to their quantum size effect and spherical nanostructures, the IR absorption of NiO nanoparticles is blue-shifted compared to that of the bulk form. The IR spectrum of NiO displays two characteristic peaks appeared at 3445 and 1629cm⁻¹ [24]. However, there is some red or blue shift, which may be due to the small particle size of the prepared NiO. The infrared absorption spectrum changes of nano-materials was due to the quantum size role of the former factors were over the latter, the peak shifts from red to blue, and vice versa red shift to occur [25]. The absorption peak in the 2362cm^{-1} was induced by the $CO₂$ in air adsorbed on the samples [26].

Fig. 6. IR absorbance spectra of NiO nanoparticles

The optical characterization of the powder sample on transparent plaster has been preformed from spectral absorbance (αt) in the wavelength range extended from 200 to 2500nm as shown in Fig. 7. The optical absorption data were analyzed using the following classical relation for near edge optical absorption in a semiconductor, *Physical Science International Journal, 4(8): 1100-1109, 2014*

of the powder sample on transparent plaster has been

the optical absorption data were analyzed using the following

optical absorption in a semiconductor,

$$
\alpha(h\nu) = \frac{K(h\nu - E_g^{\text{opt}})^{n/2}}{h\nu}
$$
\n(3)

Physical Science International Journal, 4(8): 1100-1109, 2014
wwder sample on transparent plaster has been

() in the wavelength range extended from 200 to

absorption data were analyzed using the following

sorption in a Physical Science International Journal, $4(8)$: 1100-1109, 2014

of the powder sample on transparent plaster has been

sorbance (at) in the wavelength range extended from 200 to

The optical absorption data were analyzed where *k* is a constant, E_g^{op} $E_{\ g}^{\ opt}$ is a semiconductor band gap and n a constant equal to 1* for direct transitions and 4 for indirect transition compounds [27]. The variation of $(\alpha t, h\nu)^2$ vs. (hv) for the sample is shown the inset of Fig. 7. The nature of the graphs reveals that the optical absorption in this sample takes place through direct interband transitions. The extrapolation of the linear portion of the curve to zero absorption coefficient gives the value

of optical band gap energy, E_{g}^{opt} =3.81eV. The energy gap value is in a good agreement obtained by Rifaya et al. for NiO, *opt E^g* =3.83eV [28].

Fig. 7. UV-Vis-NIR absorbance spectrum of Ni/NiO nanoparticles

4. CONCLUSION

Fine NiO nanoparticles were prepared by a homogeneous precipitation method with an aqueous solution of nickel nitrate hexahydrate and citric acid. Thermo gravimetric (TGA) analysis and differential scanning calorimeter (DSC) were used to identify the calcination temperature for obtaining a high purity of NiO powder. The experiment results for both X-ray diffraction (XRD), scanning electron microscope (SEM) show that the NiO nanoparticles are cubic structure with spherical shape and well dispersed, the particle size distribution ranging from 7 to 28nm with the average particle size is about 15.5nm. The infrared absorption band of NiO nanoparticles shows blue shifts compared with that of bulk NiO. The optical band gap energy value 3.81eV has been determined from absorbance spectra in strong absorption region.

ACKNOWLEDGMENTS

The author is grateful to El Minia University Faculty of Science Physics Department for financial support. I thank Dr. E. R. Shaaban, Al-Azhar University Faculty of Science Physics Department Assuit branch for measuring the DSC curve. Special thankfulness for Prof. Dr. MG. S. Ali El, Minia university Faculty of Science Physics department for his valuable discussion during preparing the paper.

COMPETING INTERESTS

Author has declared that no competing interests exist.

REFERENCES

- 1. Goswami DY, Vijayaraghavan S, Lu S, Tamm G. New and emerging developments in solar energy. Sol. Energy. 2004;76:33-34.
- 2. Conte M, Prosini PP, Passerini S. Overview of energy/hydrogen storage: State-of-the art of the technologies and prospects for nanomaterials. Mater. Sci. Eng. B. 2004;108:2-8.
- 3. Quan SUN, Zhong- cai SHAO, Jing- long GAO. Development in preparation and application of nano NiO J. Non- Ferrous Mining and Metallurgy. 2006;22:40-43.
- 4. Hotovy I, Huran J, Sicilano P, Capone S. Enhancement of H_2 sensing properties of NiO-based thin films with a Pt surface modification*.* J. Sensors and Actuators B. , 2004;103:300-311.
- 5. Service RF. Materials science new 'supercapacitor' promises to pack more electrical punch. Science. 2006;313:902.
- 6. Lu H, Dai W, Zheng M, Li N and Cao J. Electrochemical capacitive behaviors of ordered mesoporous carbons with controllable pore sizes. Power Sources. 2012; 209:243-250.
- 7. LeeIS, Lee N, Park J, Kim BH, Yi YW, Kim T, Kim TK, Lee IH, Paik SR, Hyeon T. Ni/NiO core/shell nanoparticles for selective binding and magnetic separation of histidine-tagged proteins. J. Am. Chem. Soc. 2006;128:10658-10659.
- 8. Yunpu Zhai, Yuqian Dou, Dongyuan Zhao, Pasquale F. Fulvio, Richard T. Mayes and Dai Sheng. Carbon materials for chemical capacitive energy storage. Adv. Mater. 2011;23:4828- 4850.
- 9. De Wael K, Verstraete A, Van Vlierberghe S, Dejonghe W, Dubruel P and Adriaens A. The electrochemistry of a gelatin modified gold electrode. Int. J. Electrochem. Sci. 2011;6:1810-1819.
- 10. Khadar MA, Biju V, Inoue A. Effect of finite size on the magnetization behavior of nanostructured nickel oxide. Mater Res Bull. 2003;38:1341-1349.
- 11. Poizot P, Laruelle S, Grugeon S, Dupont L, Tarascon JM. Nano-sized transition-metal oxides as negative-electrode materials for lithium-ion batteries.Nature. 2000;407:496- 499.
- 12. Gleiter H. Diffusion in nanocrystalline solids. Acta Mater. 2000;48:1-29.
- 13. Feldman C, Jungk HO. Polyol-mediated preparation of nanoscale oxide particles. Angew. Chem. Int. Ed. 2001;40:359-362.
- 14. Biji V, Khadar MA. Analysis of AC electrical properties of nanocrystalline nickel oxide. Mater. Sci. Eng. 2001;304:814-817.
- 15. Rodriguez-Paez JE, Caballero AC, Villeggas M, Moure C, Duran P, Fernandez JF. Controlled precipitation methods formation mechanism of ZnO nanoparticles. J Eur Ceramic Soc. 2001;21:925-930.
- 16. Alymov MI, Leontieva ON. Synthesis of nanoscale Ni and Fe powders and properties of their compacts. NanoStruct Mater. 1995;6:393-395.
- 17. Porta F, Recchia S, Bianchi C, Confalonieri F, Scari G. Synthesis and full characterisation of nickel(II) colloidal particles and their transformation into NiO. Colliods Surf (A): Physicochem Eng Aspects. 1999;155:395-404.
- 18. Llewellyn PL, Chevrot V, Ragai J, Cerclier O, Estienne J, Rouquerol F.
- 19. Preparation of reactive nickel oxide by the controlled thermolysis of hexahydrated nickel nitrate. Solid State Ionics. 1997;1293:101-103.
- 20. Alagar M, Theivasanti T, Raja A Kubera. Nanosized powder of jackfruit seed: Spectroscopic and anti*-*microbial investigative approach (1012). J. of App. Sci. 12:398- 408.
- *21.* El-Hagary M, Emam-Ismail M, Shaaban ER, Al-Rashidi A, Althoyaib S. Composition, annealing and thickness dependence of structural and optical studies on Zn_{1−*x*}Mn_xS nanocrystalline semiconductor thin films. Materials Chemistry and Physics. 2012;132:581-590.
- 22. Theivasanthi T, Alagar M. An insight analysis of nano sized Powder of Jackfruit Seed*.* Nano Biomed Eng. 2011;3:163-168.
- 23. Available: http://imagej.nih.gov/ij.
- 24. Shaaban ER.Microstructure parameters and optical properties of cadmium ferrite thin films of variable thickness. Appl Phys. 2014;115:919-925.
- *25.* Barrientos L, Rodriguez-Llamazares S, Merchani J, Jarai P, Yutronic N, Lavayen V. Unveiling the structure of Ni/Ni oxide nanoparticles system. J. Chil. Chem. Soc. 2009;54(4):391-393).
- 26. Yan-ping WANG, U Jun-wu ZH, Li li ZHANG, et al. Study on the preparation and spectral characteristics of nano-NiO. J. Spectro scopy and Spectral Analysis. 2006;26:690-69.
- 27. Li li WU, You shi WU, H ui Ying WEI, et al. Synthesis and characteristics of NiO nanowire by a solution method Materials. Materials Letters. 2004;58:2700-2703.
- 28. Moss TS. Optical properties of semiconductors. Butterworths, London 34;1961.
- *29.* Nowsath Rifaya M, Theivasanthi T, Alagar M. Chemical capping synthesis of nickel oxide nanoparticles and their characterizations studies. Nanoscience and Nanotechnology. 2012;2:134-138.

_________________________________________________________________________ *© 2014 Kaid and Ebeid; This is an Open Access article distributed under the terms of the Creative Commons Attribution License (http://creativecommons.org/licenses/by/3.0), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.*

Peer-review history: The peer review history for this paper can be accessed here: http://www.sciencedomain.org/review-history.php?iid=564&id=33&aid=5042